IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name/Description of battery	
Li-ion battery	

1a. Name/Description of the cells inside the battery Li-ion battery Cell

The test summary of the cells inside the battery must either be presented or under checkpoint 9 and 9a it must be confirmed that the UN 38.3 test summary for the cells is available.

2. Manufacturer of battery				
Name	VEKEN			
Address	No.2, Area 0212, West Zone, Free Trade Zone, Ningbo, Zhejiang Province, China			
Phone	0574-86810021			
Email	nbvkbatteryqa@mail.veken.com			
Website	http://www.vekenbattery.com/			

2a. Manufacturer of the equipment (if the battery is contained in equipment)				
Name	TCL Communication Ltd.			
Address	22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong			
Phone	86+0755 33030000			
Email	NA			
Website	www.alcatelmobile.com			

3. Test laboratory of battery				
Name	Shenzhen LCS Compliance Testing Laboratory Ltd.			
Address	1F., Xingyuan Industrial Park, Tongda Road, Bao'an Blvd., Bao'an District, Shen			
Phone	0755 82591330			
Email	Candy.li@lcs-cert.com			
Website	http://www.lcs-cert.com			

4. ID-number and date			
Unique test report identification number	LCS181102074ASA200	Date of test report	2018/12/20



IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

Li-ion battery

DESCRIPTION OF BATTERY

5. Mark the type of battery with an "•"		
Lithium ion battery	Lithium metal battery	
Lithium hybrid battery		
6. Parameters		
Mass in gram (g):	32.5±1g	
Lithium ion: Indicate watt-hour rating (Wh):		
Lithium metal: Indicate lithium metal content in gram (g):		
Lithium hybrid: Indicate lithium metal content in gram (g) and	d watt-hour rating (Wh):	
7. Physical description of battery Prismatic		
8. Model numbers		
TLp024C7		

TESTS AND RESULTS

9. List of tests conducted and results - Mark N/A, pass or fail with an "•"	N/A	pass	fail
T1 - Altitude simulation	0	•	0
T2 - Thermal Test	Ö	•	Ŏ
T3 - Vibration	Ŏ	•	Ŏ
T4 - Shock	O	•	O
T5 - External Short Circuit	O	•	Ŏ
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.	0	•	0
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.	0	•	0
T7 - Overcharge		•	0
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.	0	•	O
		O	O
	O	O	Ō

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

Li-ion battery

9a.UN 38.3 Test Confirmation for the Cells inside the battery When no separate document for the cells is provided, this confirms that the cells inside the battery (see checkpoint 1.a.) have successfully passed the UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be marked as "passed" and here under 9.a. "Cell UN 38.3 Test confirmed" needs to be ticked.	•		.l 38.3 ⁻ ofirmed	est	UN 38.	Cell 3 Test NOT irmed	\bigcirc
10. Reference to assembled battery testing requirements							
10. Reference to assembled battery testing requirements		dinson.					
						N/A	✓
11. Reference to the revised edition of the Manual of Tests and Criteria use	ed and to	o am	endme	nts the	ereto		
CST/SG/AC.10/11/Rev.6 section 38.3							
				7.00			
ADDITIONAL SUPPLIER INQUIRY							
Quality management system for manufacturing batteries Does the manufacturer of the battery manufacture the products based on documented quality management system according to transport regulations.					YES	NO	\bigcirc
13. Are the following parameters exceeded? Lithium ion battery: more than 100 Wh Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh				C	YES	NO	
Check point 14 – 16 need to be answered when 13 has been ticked "YES":							
14. Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?				0	YES	NO	\bigcirc
15. Is each battery equipped with an effective means ofventing external si	hort circu	uits?		(YES	NO	O
16. Is each battery containing collections of cells connected in parallel equipped with off cave means as necessary to prevent dangerous reverse cut arrow (e.g. diodes, fuses, etc.)?	e	$\Big)$	N/A	•	YES	NO	
17. Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion ba	attorios r	ond I	ithium	nolue	or halle	cioc	
State of Charge (SoC) max. 30 %	(((((((((((((((((((((((((((((((((((((((N/A	Porgili	YES	NO	\bigcirc

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

Li-ion battery

BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the batteries are installed in articles:					
18.a) Only button cells enclosed?					
18.b) Number of enclose	1				
When the equipment is	intentionally active/switched on during transport e	.g. data loggers:			
18.c) Confirmation that n	o dangerous amount of heat is emitted from the equip	oment N/A YES NO			
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160					
40.51					
19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature			
ozlivile	DERRINGH DAVID	TCT Mobile Europe SAS TCT Mobile Europe SAS Immeuble Le Capitole Immeuble Le Capitole Immeuble Le Capitole Immeuble Le Capitole Immeuble Le Capitole			
		TCT Mobile Le Capitole Immeuble Le Capitole 155, avenue des Champs Pierreux 92000 Nanterre - FRANCE 92000 Nanterre 440 038 222 RCS Nanterre 440 038			