

# **CE / EMC Test Report**

Report Reference No	AIT21030207E		
Applicant's name: Cyrus Technology GmbH			
Address:	Hergelsbendenstrasse 49, D-52080 Aachen, Germany		
Manufacturer 's name:	ShenZhen Sai Jiao Yang Energy &Science Technology CO.,Ltd		
Address:	Bldg.#2, Jingneng Technological and Environment industrial zone, Baolong 2nd Rd, Long'gang District, Shenzhen, 518116,China		
Test item description:			
Product name:	Polymer Lithium-ion Battery		
Trademark:	Cyrus		
Model and/or type reference :	5271165		
Rating(s):	3.7V, 8500mAh		
Testing Laboratory information:			
Testing Laboratory Name:	Dongguan Yaxu (AiT) Technology Limited		
Address	No. 22, Jinqianling Third Street, Jitigang, Huangjiang, Dongguan,		
This device described above has b results show that the equipment un applicable only to the tested sample This report shall not be reproduced	een tested by Dongguan Yaxu (AiT) Technology Limited, and the test ader test (EUT) is in compliance with the CE requirements. And it is identified in the report.		
Technology Limited, this document r personal only, and shall be noted in	nay be altered or revised by Dongguan Yaxu (AiT) Technology Limited, the revision of the document.		
Testing	:		
Date of receipt of test item			
Date (s) of performance of tests			
Date of Issue			
Test Result	Hugh		
Approved by (+ signature)			
Approved by (+ signature)	Seal Chen		



2.

3

4

5

6

7

1. Contents

		Page
1.	ER PAGE	CONTENTS
2		
TE	EST SUMMARY	3
2.1	MEASUREMENT UNCERTAINTY	4
TE	EST FACILITY	5
3.1	DEVIATION FROM STANDARD	5
3.2	ABNORMALITIES FROM STANDARD CONDITIONS	5
G	ENERAL INFORMATION	6
4.1	GENERAL DESCRIPTION OF EUT	6
4.2	TEST LOCATION	6
4.3	EUT TEST MODE	7
4.4	DESCRIPTION OF TEST SETUP	7
4.5	TEST PERIPHERAL LIST	8
4.6	EUT PERIPHERAL LIST	8
E	QUIPMENTS LIST FOR ALL TEST ITEMS	9
R	ADIATED EMISSION MEASUREMENT	11
6.	1.1 E.U.T. Operation	11
6.	1.2 Test Specification	11
6.	1.3 Measurement Data	12
6.	1.4 Test Setup photograph	15
IN	IMUNITY TEST RESULTS	16
7.1	ELECTROSTATIC DISCHARGE IMMUNITY TEST	16
7.	1.1 E.U.T. Operation	16
7.	1.2 Test specification	16
7.	1.3 Measurement Data	17
7.	1.4 Test Setup Photograph	18
7.2	RF FIELD STRENGTH IMMUNITY TEST	19

Page 2 of 24

- 7.2.1 E.U.T. Operation
- 7.2.2 **Test specification**
- 7.2.3 Measurement Data
- 7.2.4 Test Setup Photograph

7.3	POWER FREQUENCY MAGNETIC FIELD IMMUNITY TEST

- 7.3.1 E.U.T. Operation
- 7.3.2 Test specification
- 7.3.3 Measurement Data

8APPENDIX-Photographs of EUT Constructional Details

19

19

20

21 22

22

22



## 2. Test Summary

Test	Test Requirement	Test Method	Criterion	Result
Radiated Emissions 30MHz to 1GHz	EN 55032:2015+A1:2020 EN 61000-6-3-2007+A1-2012	Clause 7.3 of CISPR 16-2-3	Limits	PASS
Electrostatic Discharge	EN 55035: 2017 EN 61000-6-1:2019	IEC 61000-4-2:2008	В	PASS
R/S	EN 55035: 2017 EN 61000-6-1:2019	IEC 61000-4-3:2010	А	PASS
Power Frequency magnetic Field	EN 55035: 2017 EN 61000-6-1:2019	IEC 61000-4-8:2009	A	PASS
Note:			•	
N/A: not applicable.				
Model description:	None			



#### 2.1 Measurement Uncertainty

The report uncertainty of measurement  $y \pm U$ , where expended uncertainty U is based on a standard uncertainty Multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

No.	Item	Frequency Range	U , Value
1	Power Line Conducted Emission	150KHz~30MHz	1.20 dB
2	Disturbance Power Emission	30MHz~300MHz	2.96 dB
3	Radiated Emission Test	30MHz~1GHz	3.30 dB
4	Radiated Emission Test	1GHz~18GHz	3.30 dB



## **3 Test Facility**

The test facility is recognized, certified or accredited by the following organizations:

#### .CNAS- Registration No: L6177

Dongguan Yaxu (AiT) technology Limited is accredited to ISO/IEC 17025:2005 general Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the competence of testing and calibration laboratories) on Apr. 18, 2016

### 3.1 Deviation from standard

None

#### 3.2 Abnormalities from standard conditions

None



## **4** General Information

## 4.1 General Description of EUT

EUT Name:	Polymer Lithium-ion Battery
Model No:	5271165
Derivative models:	N/A
Brand Name:	Cyrus
Serial No:	N/A
Power Supply Range:	3.7V, 8500mAh
Test Power Supply:	Charge: DC 4.25V from DC power supply Discharge: DC 3.7V from Polymer Lithium-ion Battery

#### 4.2 Test Location

All tests were performed at:

Dongguan Yaxu (AiT) Technology Limited No. 22, Jin qianling Third Street, Jitigang, Huangjiang, Dongguan, Guangdong, China.

Tel.: +86.769.82020499 Fax.: +86.769.82020495



### 4.3 EUT Test Mode

Mode 1	The EUT is Charging.
Mode 2	The EUT is Discharging.

## 4.4 Description of Test setup

EUT was tested in normal configuration (Please See following Block diagrams)

1. Block diagram of EUT configuration-EMI					
Mode 1:					
	EUT DC Power supply				
Mode 2:					
	EUT Dummy Load				
2. Block diagram of EU	T configuration-EMS				
The same as above.					



## 4.5 Test Peripheral List

No.	Equipment	Manufacturer	EMC Compliance	Model No.	Serial No.	Power cord	signal cable
1	DC Power supply	Manson	N/A	HCS-3604	G521100129	N/A	N/A

## 4.6 EUT Peripheral List

No.	Equipment	Manufacturer	EMC Compliance	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A	N/A



## **5 Equipments List for All Test Items**

	Radiation Test Equipment						
No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date	
1	EMI Measuring Receiver	R&S	ESR	101160	2020.08.28	2021.08.27	
2	Low Noise Pre Amplifier	Tsj	MLA-10K01-B01-27	1205323	2020.08.28	2021.08.27	
3	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9160	9160-3206	2020.08.28	2021.08.27	
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2020.08.28	2021.08.27	
5	Spectrum Analyzer	ADVANTEST	R3182	150900201	2020.08.28	2021.08.27	
6	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2020.08.28	2021.08.27	
7	Broadband Horn Antenna	Schwarzbeck	BBHA 9120D	452	2020.08.28	2021.08.27	

ESD Test Equipment							
No	No Test Equipment Manufacturer Model No Serial No Cal. Date Cal. Due Date						
1	ESD Simulator	Schaffner	NSG435	5866	2020.08.28	2021.08.27	

	R/S Test Equipment											
No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date						
1	MXG analog signal generator	Agilent	N5181A	MY46240859	2020.08.28	2021.08.27						
2	Power Amplifier	Schaffner	CBA9433	T43574	2020.08.28	2021.08.27						
3	Power Amplifier	Schaffner	CBA9409	T43605	2020.08.28	2021.08.27						
4	Logarithmic-perio dic Antenna	Schwarzbeck	VULP9118E	820	2020.08.28	2021.08.27						
5	Broadband Horn Antenna	Schwarzbeck	BBHA 9120LF	255	2020.08.28	2021.08.27						
6	Power meter	Agilent	E4419B	MY45102079	2020.08.28	2021.08.27						
7	Power sensor	Agilent	8481A	MY41097696	2020.08.28	2021.08.27						
8	Power sensor	Agilent	8481A	MY41097697	2020.08.28	2021.08.27						
9	RF Relay matrix	tsj	RFM-S621	04261	2020.08.28	2021.08.27						



			Report No.: AIT21030207E									
	PFMF Test Equipment											
No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date						
1	Magnetic field generator	Schaffner	MFO6501	34299	2020.08.28	2021.08.27						
2	Magnetic Field Loop Antenna	Schaffner	INA 702	148	2020.08.28	2021.08.27						

Note:

1. is not applicable in this Test Report. Sis applicable in this Test Report.



## 6 Radiated Emission Measurement

Limits of Radiated Emi	ssion Measu	urement	(Below 1	GHz)						
			ass A (3m)	1		$\square$	Clas	s B (3	3m)	
Frequency (MHz)	Quasi-Peak dB(µV/m)				Quasi-Peak dB(µV/m)					
30 ~ 230	50.0						40	0.0		
230 ~ 1000		Į	57.0				47	<b>'</b> .0		
Limits of Radiated Emission Measurement (Above 1GHz)										
			ass A (3m)				] Class	s B (3	3m)	
Frequency (MHZ)	Peak dB(µ	ıV/m)	Average	e dB(µV/n	ר)	Peak dB(µV	/m)	Ave	erage d	B(µV/m)
1000~3000	76			56		70			50	1
3000~6000	80	80 60				74 54				
Dotoctor	Pea	k for pre-s	can (120k	Ήzι	resolution band	width)				
Quasi-Peak if maximum peak within 6dB of limit										
6.1.1 E.U.T. Operation										
Temperature:	26°C Humidity: 55% RH			ŀ	Atmospheric Pre	essure	:	101	Кра	
Test Mode:	Mode	e 1/Mod	e 2	W	orse	e Mode:		Mode 2		
6.1.2 Test Specification										
6.1.2 Test Specification										

EUT was placed upon a wooden test table which was placed on the turn table 0.8m above the horizontal metal ground plane, and operating in the mode as mentioned above. A receiving antenna was placed 3m away from the EUT. During testing, turn around the turn table and move the antenna from 1m to 4m to find the maximum field-strength reading. All peripherals were placed at a distance of 10cm between each other. Both horizontal and vertical antenna polarities were tested.



#### 6.1.3 Measurement Data

An initial pre-scan was performed in the 3m chamber using the spectrum analyzers in peak detection mode. The EUT was measured by Biology antenna with 2 orthogonal polarities and peak emissions from the EUT were detected within 6dB of the class B limit line.

The following quasi-peak measurements were performed on the EUT.





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	35.3750	27.48	-4.76	22.72	40.00	-17.28	peak
2		46.3402	25.14	-4.94	20.20	40.00	-19.80	peak
3		70.8315	27.72	-10.42	17.30	40.00	-22.70	peak
4		210.0482	23.64	-3.75	19.89	40.00	-20.11	peak
5		386.6338	26.11	-4.21	21.90	47.00	-25.10	peak
6		545.1825	23.65	1.45	25.10	47.00	-21.90	peak







#### 6.1.4 Test Setup photograph



![](_page_15_Picture_0.jpeg)

## 7 Immunity Test Results

## 7.1 Electrostatic discharge immunity test

Acceptable Performance Criterion:	В	
Discharge Impedance:	330 Ω / 150 pF	
	Air Discharge:	±8 kV
Discharge Voltage:	Contact Discharge:	±4kV
	VCP, HCP:	±4kV
Polarity:	Positive & Negative	
Minimum discharge Interval:	1 second	

#### 7.1.1 E.U.T. Operation

	101	Кра							
Test Mode: Mode 1/ Mode 2	Mode 1/ Mode 2								

#### 7.1.2 Test specification

![](_page_15_Figure_9.jpeg)

EUT was operated in the mode as mentioned above. Both contact and air discharge was executed. Contact discharge to the conductive surfaces and to coupling planes; air discharge at insulating surfaces. Each test point shall be subjected to 25 discharges at least (For each voltage and polarity).

![](_page_16_Picture_0.jpeg)

## **Test Record**

Electrostatic Discharge Test Results																		
M/N:	52	5271165								Test Result: 🛛 Pass 🗌 Fail								
Test Voltage:	Ch Dis Lit	harge: DC 4.25V from DC power supply vischarge: DC 3.7V from Polymer ithium-ion Battery								Test date: 2021.03.02								
Discharge times	DischargeContact discharge: minimum 25 times (+/-respectively) at each point,timesAir discharge: minimum 10 times (+/- respectively) at each point.																	
Discharge Mode		Air Discharge					Contact Discharge					Performance	Docult					
Test level(kV)	4	4	8	8	1	0	1	5		2	4	4 6		6		8	Criterion	Result
Test Location	+	-	+	-	+	-	+	-	+	-	+	-	+	-	+	-		
HCP											А	А						Pass
VCP											А	А					В	Pass
A1	А	А	А	А														Pass
Note: " <b>P</b> " mea " <b>Cx</b> " means Co	Note: " <b>P</b> " means Pass, Horizontal Coupling Plane ( <b>HCP</b> ) and Vertical Coupling plane ( <b>VCP</b> ). " <b>Cx</b> " means Contact Point ,x=1 $\sim$ N, " <b>Ax</b> " means Air Point, x=1 $\sim$ N.																	

![](_page_17_Picture_0.jpeg)

#### 7.1.4 Test Setup Photograph

![](_page_17_Picture_4.jpeg)

Dongguan Yaxu (AiT) Technology Limited No. 22, Jinqianling Third Street, Jitigang, Huangjiang, Dongguan, Guangdong, China.

![](_page_18_Picture_0.jpeg)

## 7.2 RF field strength immunity test

Acceptable Performance Criterion:	В
Test Level	3V/m
Test Distance	3 m
Frequency Range	80MHz~1000MHz, 1800 MHz ,2600MHz,3500 MHz, 5000 MHz, 1400~6000 MHz 3V/m
Polarity:	Horizontal & Vertical

#### 7.2.1 E.U.T. Operation

Temperature:	26°C	Humidity:	55% RH	Atmospheric Pressure:	101	Кра							
Test Mode:		Mode 1/Mode 2											
7.2.2 Test specification													
	SG Power Amplifier GPIB Controller Syste		Fiber	3m Meter EUT 0.8m(h)									

Test was executed in a fully Anechoic chamber. An antenna was used to transmit interference signal. EUT was placed upon a wooden table above the reference ground 0.8m, and was positioned so that the four sides of the EUT shall be exposed to the electromagnetic field in a sequence. In each position the performance of the EUT was investigated. A camera was used to monitor the loss of function or degradation of performance of the EUT.

![](_page_19_Picture_0.jpeg)

#### 7.2.3 Measurement Data

## **Test Record**

M/N:	527116	5		Test Result: 🛛 Pass 🗌 Fail					
Test Voltage:	Charge Dischar Lithium	: DC 4.25V from DC powe rge: DC 3.7V from Polyme -ion Battery	er supply er	Test date: 2021.03.02					
Test Port		Enclosure							
Operating Mode		Mode 1/Mode 2							
Test Level		<u>3</u> V/m(r.m.s) ( ur	nmodulate	d )	Criterion A				
Frequenc Range(MH	cy H <sub>Z</sub> )	Antenna polarity	N	lodulation	EUT position	Result			
80~1000 1800 2600 3500					Front	Pass			
					Rear	Pass			
		Userissistal		1KHz,	Left	Pass			
		Honzontai	80% AN	80% AM	Right	Pass			
1400~600	00				Тор	Pass			
					Bottom	Pass			
	_				Front	Pass			
80~1000 1800	)				Rear	Pass			
2600 2500		Vertical		1KHz,	Left	Pass			
5000 5000		ventical		80% AM	Right	Pass			
1400~600	00				Тор	Pass			
					Bottom	Pass			

![](_page_20_Picture_0.jpeg)

#### 7.2.4 Test Setup Photograph

![](_page_20_Picture_4.jpeg)

![](_page_21_Picture_0.jpeg)

## 7.3 Power frequency magnetic field immunity test

Acceptable				
Performance Criterion:	۸ 			
Test Level:	1 A/m			
Coil Orientation:	X & Y & Z			
Test Duration:	5 Minutes for each orientation			

#### 7.3.1 E.U.T. Operation

Temperature:	26°C	Humidity:	55% RH	Atmospheric Pressure:	101	Кра
Test Mode:			Mod	e 1/Mode 2		

#### 7.3.2 Test specification

![](_page_21_Figure_8.jpeg)

The equipment is configured and connected to satisfy its functional requirements. It was placed on the ground reference plane with the interposition of a 0.1 m thickness wooden support and was placed in the center of the induction coil. All cables (include power cord and signal line) were exposed to the magnetic field for at least 1m of their length.

![](_page_22_Picture_0.jpeg)

Page 23 of 24

Pass.

Remark:

There is no need for Power Frequency Magnetic Field Immunity test to be performed on this product in accordance with EN 55035& EN61000-6-1 TABLE 1 because this product does not contain any devices susceptible to magnetic fields.

![](_page_23_Picture_0.jpeg)

#### 8APPENDIX-Photographs of EUT Constructional Details

![](_page_23_Picture_4.jpeg)

\*\*End of report\*\*