

# MSDS Report

**Samples:** Rechargeable Li-ion Battery GS35E

**Supplier Unit:** SUNWODA ELECTRONIC CO., LTD

**Supplier Address:** No.2, Yihe Rd, Shilong Community, Shiyuan Street,  
Baoan District, Shenzhen City, China

**MSDS No.:** MSDS2023010103

**Release Date:** Jan. 01, 2023



## Material Safety Data Sheet

地址：中国浙江省金华市兰溪市兰江街道雁洲路 111 号-3 栋，4 栋

Address: Building 3 and building 4, No.111 Yanzhou Rd., Lanjiang St., Lanxi County, Jinhua City, Zhejiang Province P.R. China

**Section 1 – Chemical Product and Company Identification**

**Product Name: Rechargeable Li-ion Battery**

**Sample Code: GS35E**

**GPN: G823-00380-01**

**Manufacturer: Zhejiang Sunwoda Electronic Co., Ltd.**

**Address: Building 3 and building 4, No.111 Yanzhou Rd., Lanjiang St., Lanxi County, Jinhua City, Zhejiang Province.**

**Post Code: 518108**

**Tel: 0755-29516888**

**Emergency Telephone: 0755-29516888**

**Fax: 0755-29516999**

**E-mail: [zhangyuxia@sunwoda.com](mailto:zhangyuxia@sunwoda.com)**

地址：中国浙江省金华市兰溪市兰江街道雁洲路 111 号-3 栋，4 栋

Address: Building 3 and building 4, No.111 Yanzhou Rd., Lanjiang St., Lanxi County, Jinhua City, Zhejiang Province  
. R. China

## Section 2 – Composition/Information on Ingredient

主要成分	CAS NO.	wt%
Lithium cobaltate 钴酸锂	12190-79-3	30~50
Graphite 石墨	7782-42-5	15~30
Aluminium 铝	7429-90-5	5~10
Copper 铜	7440-50-8	5~10
Carbon Black 炭黑	1333-86-4	0~2
Carboxymethyl cellulose 羧甲基纤维素	9004-32-4	0~1
POLY(PROPYLENE-CO-ETHYLENE) 1-丙烯与乙烯的聚合物	9010-79-1	0.3~1.5
Polyvinylidene fluoride 聚偏氟乙烯树脂	24937-79-9	0~2
Benzene, ethenyl-, polymer with 1,3-butadiene 聚苯乙烯丁二烯共聚物	9003-55-8	0~1.5
Aluminum oxide (Al <sub>2</sub> O <sub>3</sub> ) (9CI) 氧化铝	11092-32-3	0~1.5
polyethylene 聚乙烯	9002-88-4	0~1
Nickel 镍	7440-02-0	0.1~2
4-Fluoro-1,3-dioxolan-2-one 氟代碳酸乙烯酯	114435-02-8	0-5
Ethylene carbonate 碳酸乙烯酯	96-49-1	0-10
Diethyl carbonate 碳酸二乙酯	105-58-8	0-10
Propylene carbonate 碳酸丙烯酯	108-32-7	0-10
Lithium hexafluorophosphate 六氟磷酸锂	21324-40-3	0~5
1,3-Propanesultone 1,3-丙烷磺内酯	1120-71-4	0-0.5

## Section 3 – Hazards Identification

### Health Hazards (Acute and Chronic)

These chemicals are contained in a sealed can .Risk of exposure occurs only if the battery is mechanically or electrically abused. Contact of electrolyte and extruded lithium with skin and eyes should be avoided.

### Sign/Symptoms of Exposure

A shorted lithium battery can cause thermal and chemical burns upon contact with the skin. May be a reproductive hazard.

## Section 4 – First Aid Measures

### Eyes

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

### Skin

Remove contaminated clothes and rinse skin with plenty of water of shower for 15 minutes. Get medical aid.

地址：中国浙江省金华市兰溪市兰江街道雁洲路 111 号-3 栋，4 栋

Address: Building 3 and building 4, No.111 Yanzhou Rd., Lanjiang St., Lanxi County, Jinhua City, Zhejiang Province P.R. China

## **Inhalation**

Remove from exposure and move to fresh air immediately. Use oxygen if available.

## **Ingestion**

Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

## **Section 5 – Fire Fighting Measures**

**Flash Point:** N/A

**Auto-Ignition Temperature:** N/A

**Extinguishing Media:** Dry powder, CO<sub>2</sub>

**Special Fire-Fighting Procedures:** Self-contained breathing apparatus.

**Unusual Fire and Explosion Hazards:** Cell may vent when subjected to excessive heat exposing battery contents.

**Hazardous Combustion Products:** Carbon monoxide, carbon dioxide, lithium oxide fumes.

## **Section 6 – Accidental Release Measures**

### **Steps to be Taken in case Material is Released or Spilled**

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can.

The preferred response is to leave the area and allow the batteries to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

### **Waste Disposal Method**

It is recommended to discharge the battery to the end, handing in the abandoned batteries to related department unified, dispose of the batteries in accordance with approved local, state, and federal requirements. Consult state environmental protection agency and/or federal EPA.

地址：中国浙江省金华市兰溪市兰江街道雁洲路 111 号-3 栋，4 栋

Address: Building 3 and building 4, No.111 Yanzhou Rd., Lanjiang St., Lanxi County, Jinhua City, Zhejiang Province P.R. China

## **Section 7 –Handling and Storage**

The batteries should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container.

Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire.

Do not crush or puncture the battery, or immerse in liquids.

### **Precautions to be taken in handling and storing**

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change .Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

### **Other Precautions**

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

## **Section 8 –Exposure Controls, Personal Protection**

### **Respiratory Protection**

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting batteries. Respiratory Protection is not necessary under conditions of normal use.

### **Ventilation**

Not necessary under conditions of normal use.

### **Protective Gloves**

Not necessary under conditions of normal use.

### **Other Protective Clothing or Equipment**

Not necessary under conditions of normal use. Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

## **Section 9 –Physical and Chemical Properties**

**Nominal Voltage: 3.89V**

**Rated Capacity: 4485mAh**

**Appearance characters:** odorless, solid battery.

## **Section 10 –Stability and Reactivity**

### **Stability**

Stable

### **Conditions to Avoid**

Heating, mechanical abuse and electrical abuse.

**Hazardous Decomposition Products** N/A.

**Hazardous Polymerization** N/A.

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalis, halogenated hydrocarbons.

## **Section 11 –Toxicological Information**

Inhalation, skin contact and eye contact are possible when the battery is opened.

Exposure to internal contents, the corrosive fumes will be very irritating to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibrosis lung injury and membrane irritation.

## **Section 12 –Ecological Information**

When promptly used or disposed the battery does not present environmental hazard. When disposed, keep away from water, rain and snow.

地址：中国浙江省金华市兰溪市兰江街道雁洲路 111 号-3 栋，4 栋

Address: Building 3 and building 4, No.111 Yanzhou Rd., Lanjiang St., Lanxi County, Jinhua City, Zhejiang Province P.R. China

**Section 13 –Disposal Considerations**

**APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARTION**

If batteries are still fully charged or only partially discharged, they can be considered a reactive hazardous waste because of significant amount of not creation, or unconsumed lithium remaining in the spent battery. The batteries must be neutralized through an approved secondary treatment facility prior to disposal as a hazardous waste. Recycling of battery can be done in authorized facility, through licensed waste carrier.

**Section 14 –Transport Information**

The battery models listed have a Watt-hour rating of no more than 100Wh. And shipment contains no item listed under IATA DGR Special Provision A154 and meets all requirements under UN Manual of Tests and Criteria Part III, subsection 38.3.

No	ITEMS	RESULT	REMARKS
1	Altitude simulation	Pass	Test 1 to 5 must be conducted in sequence on the same cell or battery
2	Thermal test Vibration	Pass	
3	Shock	Pass	
4	External short circuit	Pass	
5	Impact/Crush	Pass	
6	Altitude simulation	Pass	
7	Overcharge	Pass	Only battery with an overcharge condition do need this test item

地址：中国浙江省金华市兰溪市兰江街道雁洲路 111 号-3 栋，4 栋

Address: Building 3 and building 4, No.111 Yanzhou Rd., Lanjiang St., Lanxi County, Jinhua City, Zhejiang Province P.R. China

8	Forced charge	Pass	
---	---------------	------	--

The International Air Transport Association (IATA) Dangerous Goods Regulations (64th Edition, 2023). Packing instruction 965 Section IB for Lithium ion battery. (When shipping batteries "packing with "or "contained in" equipment, use packing instruction 966 or 967 as appropriate). Each package (battery only) is capable of withstanding a 1.2m drop test in any orientation without damage to cells or batteries contained therein, without shifting of the contents so as to allow battery to battery (or cell to cell ) contact and without release of contents. The net quantity of lithium ion batteries (or cells) does not exceed 10Kg for each package.

And the net quantity of lithium ion batteries (or cells) does not exceed 5Kg (Passenger aircraft) or 35Kg (Cargo Aircraft Only) when shipping batteries "packing with "or "contained in" equipment The product is not subject to the other provisions of IMO IMDG Code (Amend 40-20) according to Special Provision188.

The product is not subject to the other provisions of RID/ADR Code (2021 Edition) according to Special Provision188.

Packaging complies with the requirements of the International Civil Aviation Organization (ICAO) Technical Instructions (2023-2024 Edition).

Label master at <http://www.labelmaster.com>. Separate battery when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and get wet by rain.

**Transport Fashion:** By air , sea or land

## Section 15 –Regulatory Information

### Law Information

《Dangerous Goods Regulation》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

地址：中国浙江省金华市兰溪市兰江街道雁洲路 111 号-3 栋，4 栋

Address:Building 3 and building 4, No.111 YanzhouRd., Lanjiang St.,Lanxi County, Jinhua City, Zhejiang ProvinceP .R. China



- 《Technical Instructions for the Safe Transport of Dangerous Goods》
- 《Classification and code of dangerous goods》
- 《Occupational Safety and Health Act》 (OSHA)
- 《Toxic Substances Control Act》 (TSCA)
- 《Consumer Product Safety Act》 (CPSA)
- 《Federal Environmental Pollution Control Act》 (FEPCA)
- 《The Oil Pollution Act》 (OPA)
- 《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》 (SARA)
- 《Resource Conservation and Recovery Act》 (RCRA)
- 《Safety Drinking Water Act》 (CWA)
- 《California Proposition 65》
- 《Code of Federal Regulations》 (CFR)

In accordance with all Federal, State and Local laws.

#### **Section 16 –Additional Information**

The above information is based on the date of which we are aware and is believed to be correct as of data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material of his particular purpose.

地址：中国浙江省金华市兰溪市兰江街道雁洲路 111 号-3 栋，4 栋

Address: Building 3 and building 4, No.111 Yanzhou Rd., Lanjiang St., Lanxi County, Jinhua City, Zhejiang Province P.R. China

